

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1 to 17. (Canceled).

18. (Currently Amended) [[The]] A method for transmitting signaling and control information for a wavelength-division multiplex network that performs an optical, fiber-bound information transfer in a digitized form, comprising according to claim 16, wherein:

- using a terminal to process useful information according to one of an optical encoding and an optical decoding;
- performing one of:
 - feeding at a network terminator the useful information into the wavelength-division multiplex network as an optical signal having a defined fundamental wavelength, and
 - removing at the network terminator the useful information from the wavelength-division multiplex network as the optical signal having the defined fundamental wavelength;
- transmitting collectively a plurality of signals having different wavelengths in an optical fiber;
- performing one of a generation and an analysis of the signaling and control information in one of the network terminator and in a further network element;
- performing one of:
 - feeding the signaling and control information into the wavelength-division multiplex network, and
 - removing the signaling and control information from the wavelength-division multiplex network;
- using a time-division multiplex operation to transmit the signaling and control information with the defined fundamental wavelength via the same components of the wavelength-division multiplex network as the corresponding useful information, wherein the signaling and control information is modulated independently of the useful information; and
- transmitting the signaling and control information at regular time intervals T for a predetermined duration of T_{OH} .

wherein the signaling and control information includes a characteristic signal sequence by which the signaling and control information is capable of being identified in a signal stream of the useful information such that corresponding transmitters and receivers of the signaling and control information are synchronized,

and wherein a synchronization between a transmitter and a receiver of the signaling and control information being ~~[[is]]~~ accomplished by a characteristic signal being transmitted at brief intervals, and following the synchronization, the characteristic signal being ~~[[is]]~~ transmitted at variable duration time intervals that gradually increase up to a duration of the regular time intervals T.

19. (Currently Amended) ~~[[The]]~~ A method for transmitting signaling and control information for a wavelength-division multiplex network that performs an optical, fiber-bound information transfer in a digitized form, according to claim 16, further comprising the step of:

using a terminal to process useful information according to one of an optical encoding and an optical decoding;

performing one of:

feeding at a network terminator the useful information into the wavelength-division multiplex network as an optical signal having a defined fundamental wavelength, and

removing at the network terminator the useful information from the wavelength-division multiplex network as the optical signal having the defined fundamental wavelength;

transmitting collectively a plurality of signals having different wavelengths in an optical fiber;

performing one of a generation and an analysis of the signaling and control information in one of the network terminator and in a further network element;

performing one of:

feeding the signaling and control information into the wavelength-division multiplex network, and

removing the signaling and control information from the wavelength-division multiplex network;

using a time-division multiplex operation to transmit the signaling and control information with the defined fundamental wavelength via the same components of the wavelength-division multiplex network as the corresponding useful information, wherein the signaling and control information is modulated independently of the useful information;

transmitting the signaling and control information at regular time intervals T for a predetermined duration of T_{OH} ; and

during the transmission of the signaling and control information, interrupting the transmission of the useful information for a duration of $T_{OH} + 2\delta$, wherein the time interval δ

exists between a suppression of the useful information and the transmission of the signaling and control information,

wherein the signaling and control information includes a characteristic signal sequence by which the signaling and control information is capable of being identified in a signal stream of the useful information such that corresponding transmitters and receivers of the signaling and control information are synchronized.

20. (Previously Presented) The method according to claim 19, further comprising the steps of:

 during the interruption lasting for the duration of $T_{OH} + 2\delta$ resulting from the transmission of the signaling and control information, buffering the useful information in a transmitting terminal equipment; and

 during an intervening interval with a duration of $T - (T_{OH} + 2\delta)$, transmitting the useful information at such an increased bit rate that an average bit rate corresponds to an uninterrupted useful information transfer.

21. (Previously Presented) The method according to claim 20, wherein the transmitting terminal equipment includes shift registers.

22. (Previously Presented) The method according to claim 20, further comprising the steps of:

 causing the transmitting terminal equipment to reserve time gaps of the duration $T_{OH} + 2\delta$ in the useful information; and

 causing the transmitting terminal equipment to signal a temporal position of the reserved time gaps via the network terminator to a network element transmitting the signaling and control information.

23. (Previously Presented) The method according to claim 20, further comprising the steps of:

 causing the network terminator to inform the transmitting terminal equipment of when a time gap having the duration of $T_{OH} + 2\delta$ in the useful information is to be reserved for the transmission of the signaling and control information; and

 causing the network terminator to inform the transmitting terminal equipment of when the useful information is to be buffered.

24. (Canceled).

25. (Canceled).

26. (Canceled).

27. (Previously Presented) The method according to claim 20, further comprising the steps of:

- causing the network terminator to communicate the signaling and control information to the transmitting terminal;

- causing the transmitting terminal to optically encode the signaling and control information and transmit the signaling and control information via the wavelength-division multiplex network; and

- causing a receiving terminal provided with the encoded useful information to:

- decode the signaling and control information,

- filter out the signaling and control information from the useful information,

- and

- communicate the signaling and control information to an upstream receiver-end network terminator.

28. (Canceled).